



- TEMPEST Level B
- 55 Inch
- Resolution 4K UHD
- Only 29 mm deep

Monitor 55" TEMPEST Level B

Description

The 55" TEMPEST Level B and RÖS U2 certified monitor features a 4K panel with two HDMI inputs, making it ideal for use as an additional monitor in Fibersystem's video conferencing systems or when connected to one of Fibersystem's computers. It is based on Samsung QMC.

The monitor is anti-glare and ensures optimal visibility from all angles and at any time of day, providing clear and legible information under all lighting conditions.

Security-enhancing features

- TEMPEST Level B SDIP-27
- RÖS U2
- No wireless network or Bluetooth (No-Radio)

Features

- 2x HDMI 4K.
- Resolution 3840 x 2160 (4K UHD)

Accessories

- VTC Floor Stand Motorized
- VTC Floor Stand Manual
- VTC Wall mount



Wallmount



Floor Stand

Features

Features	Description
Display size	55"
Display area	1210 x 680 (WxH) mm
Optimal (recommended) resolution	3840 x 2160 @ 60 Hz
Brightness (typical)	500 cd/m2 (Candela/ square meter)
Contrast	4000:1
Viewing angle (Horizontal/Vertical)	178/178°
Response time (typical)	8 ms
Panel type	VA (Vertical alignment)

Technical data

I/O-ports	Description
Video input HDMI	2xHDMI 4K
Power supply	Description
Mains voltage	100-240 VAC, 50-60 Hz
Connector	IEC 320-C7
Power consumption, typical	110 W
Power consumption, maximum	145 W
Mechanics and environment	Description
Dimensions	709 x 1238 x 29 (HxWxD) mm
Weight	15,7 kg
Operating temperature	0 °C to 40 °C, at 10–80% RH relative humidity, non-condensing
Storage temperature	-20 °C to 60 °C, at 10–80% RH relative humidity, non-condensing

Ordering information

Product	Product No
Monitor 55" TEMPEST Level B	50-70-3148
Parts included	Product No
Remote control	50-70-3154
Original power cable	N/A
Accessories	Product No
VTC Floor Stand Motorized	60-00-7684
VTC Floor Stand Manual	60-00-7683
VTC Wall mount	60-00-7685