



- RÖS U1
- TEMPEST Level A+
- Resolution WUXGA
- 6500 Lumen
- Viewing area up to 500"
- Fiber Optic HDMI 4K
- Fiber Optic DVI Full HD

Projector V7 TEMPEST Level A+ and RÖS U1

Description

Projector V7 U1/LA+ is based on the Epson EB-L690U with safety-enhancing features and modifications to achieve TEMPEST Level A+ and RÖS U1.

The projector supports both fiber optic HDMI (4K) and DVI (FullHD) and connects to Fibersystems Computer solutions and is intended to be used in meeting rooms with a need for larger presentation areas.

If the projector is intended to be used with, for example, a computer with a regular HDMI, Fibersystems HDMI-HDMI FO Converter is needed, see the image below and under accessories.

The projector can be mounted on a ceiling with a ceiling mount (see accessories) or stand on a table and then adjusted with integrated, adjustable legs on the bottom of the projector.

Safety-enhancing features

- RÖS U1
- TEMPEST Level A+ SDIP-27

Components

- Remote Control V7 U1/LA+
- Power cable 2 m

Accessories

- Ceiling bracket incl shaft 220-260 mm
- Ceiling bracket incl shaft 450-700 mm
- Ceiling bracket incl shaft 700-1250 mm
- HDMI-HDMI FO (Fiber Optic) Converter
 - a) To connect the projector to i.e a computer with a standard HDMI output



HDMI-HDMI FO Converter

Features	Description		
Resolution	WUXGA		
Brightness	6500 Lumen		
Format	16:10/16:9/4:3		
Keystone correction	Yes		
Light source	Laser		
Zoom/Focus	Manual		
Projection Distance	1,21-9,9 m		
Operating noise level, typical	25 dB		
Operating noise level, max	27 dB		
I/O-portar	Description	Connector	No
Video input 1	Fiber Optic DVI Full HD/60Hz	LC	1
Video input 2	Fiber optic HDMI 4K/60Hz	MPO	1
Power supply	Description	Connector	No
Mains voltage	AC 100 V - 240 V, 50 Hz - 60 Hz	IEC 320-C14	1
Power consumption typical	250 W		
Power consumption max	350 W		
Mechanics & Environment	Description		
Dimensions	500x440x165 mm (Width x Depth x Height with feet)		
Weight	10 kg		
Temperature drift	0 °C to 40 °C, at 20-80% RH relative humidity, non-condensing		
Temperature storage	-10 °C to 60 °C, at 10-90% RH relative humidity, non-condensing		

Ordering information

Product	FBET	FBEN	Product number
Projector V7 TEMPEST Level A+	N/A	N/A	60-00-8845

Accessories	FBET	FBEN	Product number
Ceiling mount V7 220-260 mm	M1380-131210	N/A	60-00-9211
Ceiling mount V7 450-700 mm	M1380-131310	N/A	60-00-9212
Ceiling mount V7 700-1250 mm	M1380-131410	N/A	60-00-9213
HDMI-HDMI FO Converter	M3199-998724	N/A	60-00-7909