



- 75 Inch
- TEMPEST Level B
- RÖS U2
- Resolution
3,840x2,160
- Only 28.5 mm deep

Monitor 75" TEMPEST Level B & RÖS U2

Description

Monitor 75" TEMPEST Level B and RÖS U2 features a 4K UHD screen with two electrical HDMI connections and is suitable for use as an additional monitor in Fibersystem's video conferencing system or by connecting it to one of Fibersystem's computers.

The display is anti-glare and provides excellent visibility from all viewing angles at any time of day, ensuring that the information on the screen is always clearly visible.

Security-enhancing features

- TEMPEST Level B SDIP-27
- RÖS U2
- No wireless network or Bluetooth (No-Radio)

Features

- 4K @ 60 Hz, 75" display
- Two electrical HDMI connections
- Resolution: 3840 x 2160

Accessories

- VTC Motorized Floor Stand
- VTC Manual Floor Stand
- VTC Wall Mount



Wall mount



Floor stand

Features

Features	Description
Screen size	75"
Resolution	3840x2160 (W x H) mm
Brightness (typical)	500 nit
Contrast	4000:1
Viewing angle (Horizontal/vertical)	178/178°
Response time (typical)	8 ms
Panel type	VA

Technical data

I/O ports	Description	Connector	Quantity
HDMI video input	Electrical HDMI 4K @ 60 Hz	HDMI	2
Power supply	Description		
Mains voltage	100-240 VAC, 50-60 Hz		
Connection	IEC 320-C14		
Typical power consumption	214.5 W		
Power consumption, sleep mode	0.5 W		
Mechanical and environmental	Description		
Dimensions	960x1680x28.5 (H x W x D) mm		
Weight	33.4 kg		
Operating temperature	0 °C to 40 °C, at 10-80% RH relative humidity, non-condensing		
Storage temperature	-20 °C to 60 °C, at 10-80% RH relative humidity, non-condensing		

Ordering information

Main product	Product No
Monitor 75" TEMPEST Level B	60-00-9181
Included components	Product No
Remote control	50-70-3154
Original power cable	50-65-5710
Accessories	Product No
VTC Motorized Floor Stand	60-00-7684
VTC Manual Floor Stand	60-00-7683
VTC Wall Mount	60-00-7685