



Graphic converter HDMI-HDMI Fo

Description

Graphic Converter HDMI–HDMI Fiber is designed to convert an HDMI input/output into a Fibersystems fiber optic HDMI interfaces. It allows external computers with an HDMI output to be connected against Fibersystems RÖS U1 and TEMPEST Level A products such as VTC systems, monitors and projectors.

The Graphic Converter can also be used to connect Fibersystem's fiber optic HDMI sources, such as screen clients and document cameras, to external monitors and projectors.

The Graphics Converter's HDMI input and output support resolutions up to 4K at 60Hz. Fiber connection is done via an MPO-12 connector for multi-mode fiber.

Accessories (examples)

- 55" Monitor TEMPEST Level A & RÖS U1
- Projector V7 TEMPEST Level A & RÖS U1
- Document camera TEMPEST Level A & RÖS U1

Technical data

I/O-ports	Description	Connectors	No
Video In 1	HDMI 4K/60 Hz	HDMI	1
Video Out 1	HDMI 4K/60 Hz	HDMI	1
Video In 2	MPO Multimode 850/1300 nm	MPO-12 Female	1
Power supply		Description	
Mains voltage	100-240 VAC, 50-60 Hz		
Connector	IEC 60320 C14		
Power consumption typical	7 W		
Power consumption max	10 W		
Mechanics and Environment		Description	
Dimensions	32x130x217 (HxWxD) mm		
Vikt	1 kg		
Drifttemperatur	0 - 35 °C at 10-90%RH relative humidity, non-condensing		
Operating temperature	-20 - 60 °C at 10-90%RH relative humidity, non-condensing		

Ordering information

Product	Product No
Graphic Converter HDMI-HDMI Fo	60-00-7909
Tillbehör	Product No
55" Monitor TEMPEST Level A	60-00-7728
Projector V7 TEMPEST Level A	60-00-8845
Document camera TEMPEST Level A	60-00-7776