



- TEMPEST Level A
- RÖS U1
- Print speed 33 ppm
- Print quality up to 1200 x 1200 dpi

Color Laser Printer USB2.0 V2 TEMPEST Level A

Description

The printer is a TEMPEST Level A and RÖS U1 certified color laser printer. It is based on Xerox C320, has double-sided printing and a print speed of 33 pages per minute. The touch screen on the printer makes it easy to navigate.

Printing is done seamlessly by connecting a computer via USB 2.0 fiber optic or by connecting the printer to the network via the 100Mbps Ethernet fiber optic connection.

Safety-enhancing features

- TEMPEST Level A SDIP-27
- RÖS U1
- No Wi-Fi, Bluetooth or NFC

Features

- Print speed: 33 ppm
- Printing Technology: Laser
- Print quality: 1200 x 1200 dpi
- Double-sided printing

Operating system support

Windows Server 2012, Windows Server 2012 R2, Windows Server 2019, Windows Server 2022, Windows® 10, Windows® 11, macOS 11.x, macOS 12.x, macOS 13.x

Features

Features	
Print speed	33 ppm
Printing technology	Laser
Print quality	600 x 600 dpi, 4800 Color Quality
Paper handling	Up to 250 sheets
Paper format	98 x 148 mm to 216 x 356 mm
Printing media	Plain paper, light paper, heavy paper, cardboard paper, labels, envelopes
Output capacity	170 sheets
Print memory	1 GB
Printing functions	Booklet Layout, Collate, Draft Mode, Duplex, Earth Smart Settings, Multiple Pages Per Sheet, Normal, One Touch UI, Orientation, Print Job ID in Margins, Print Quality, Rotate Image 180 Degrees, Saved Settings, Saved Job Types and Sample Sets, Protected Print, Tray and Toner Status, Watermark
Processor speed	1.0 GHz
OS support	Windows Server 2012, Windows Server 2012 R2, Windows Server 2019, Windows Server 2022, Windows® 10, Windows® 11, macOS 11.x, macOS 12.x, macOS 13.x
Printer language	Instant Image, HTML, PCL 5, PCL® 6 Emulation, PDF v1.7 Emulation, PostScript® 3 Emulation, XPS

Technical data

I/O-ports	Description	Connector	No
Fiber optical USB	Fiber optical USB 2.0	LC	1
Network 100 Mbps	Fiber optical 100 Mbps Ethernet	SC	1
Power supply		Description	
Mains voltage	230 VAC, 50-60 Hz		
Connector	IEC 320-C14		
Power consumption printing	587 W		
Mechanics and Environment		Description	
Dimensions	455 x 423 x 318 mm (BxWxH)		
Weight	21 kg		
Operating temperature	10 °C to 32.5 °C, at 30-70%RH relative humidity, non-condensing		
Storage temperature	-20 °C to 40 °C, at 0-95%RH relative humidity, non-condensing		

Order information

Product	Product No
Color Laser Printer USB2.0 V2 TEMPEST Level A	60-00-9204